



Data Sheet

Single Contactor

General Information:



Danfoss single Contactor is max 40 or 60 amp load Contactor. This Contactor can be activated by all Danfoss controllers.

Technical Data:

Max. Lead Voltage:	600 V
Max. Heating Load:	40 /60A
Control Voltage:	120 V
Enclosure Type:	NEMA 1
Mounting:	Wall mounted
Dimensions:	8.75" x 5" x 4"

Ordering Information:

Part No.	Description:
088L3450	Single Contactor, 3P, 120 V
088L3451	Single Contactor, 3P, 208-240 V

Application:

Part No.	Description:
088L5130	Programmable Thermostat with Floor Sensor
088L5132	Programmable Thermostat with Air Sensor
088L5133	Non-Programmable Thermostat with Floor Sensor
088L3415	GX850M Dual Zone Controller
088L3035	DS-2C Snow Melt Controller (30A)
088L3037	DS-5C Snow Melt Controller (60A)

Warranty:

Danfoss offers a two year limited warranty covering defects in workmanship and materials.

Technical Services:

For technical questions, please contact **Comfort Radiant Heating (888)448-0555** or find more **Danfoss products at www.danfossradiant.com**

Danfoss can accept no responsibility for possible errors in catalogs, brochures, other printed materials, and website information. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alteration can be made without subsequent changes being necessary in specifications already agreed upon. All trademarks in this material are property of the respective companies. Danfoss and Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Comfort Radiant Heating LLC

Tel: 1-518-373-5700
 info@danfossradiant.com
 www.DanfossRadiant.com